



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 13.04.2016

Revision: 13.04.2016

1 Identification of the substance/mixture and of the company/undertaking

· **Product identifier**

· **Trade name:** NC Beits Kleuren

· **Article number:** 02.NCXXXX.XX

· **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.

· **Application of the substance / the mixture** Coating compound/ Surface coating/ paint

· **Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

Wasziederij "De Vesting B.V."
Trasweg 12
NL-5712 BB Someren-Eind
The Netherlands
Tel: +31 493 496760
Fax: +31 493 493670

Email: vesting@euronet.nl

Web: www.vesting.nl

· **Further information obtainable from:** Product safety department.

· **Emergency telephone number:** During normal opening times: +31 493 496 760

2 Hazards identification

· **Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS08 health hazard

STOT SE 2 H371-H336 May cause damage to organs. May cause drowsiness or dizziness.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.
Acute Tox. 4 H312 Harmful in contact with skin.
Acute Tox. 4 H332 Harmful if inhaled.
Skin Irrit. 2 H315 Causes skin irritation.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.04.2016

Revision: 13.04.2016

Trade name: NC Beits Kleuren

(Contd. of page 1)

Eye Irrit. 2 H319 Causes serious eye irritation.

· **Label elements**· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

· **Hazard pictograms**

GHS02 GHS07 GHS08

· **Signal word** Danger· **Hazard-determining components of labelling:**

2-butoxyethanol
 1-methoxy-2-propanol
 n-butyl acetate
 methanol

· **Hazard statements**

H225 Highly flammable liquid and vapour.
 H302+H312+H332 Harmful if swallowed, in contact with skin or if inhaled.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H371-H336 May cause damage to organs. May cause drowsiness or dizziness.

· **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P260 Do not breathe mist/vapours/spray.
 P370+P378 In case of fire: Use for extinction: CO₂, sand, extinguishing powder.
 P403+P235 Store in a well-ventilated place. Keep cool.
 P404 Store in a closed container.

· **Additional information:**

Keep out of the reach of children

· **Other hazards**· **Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterisation: Mixtures**· **Description:** Mixture of substances listed below with nonhazardous additions.· **Dangerous components:**

CAS: 64-17-5	ethanol	25-50%
EINECS: 200-578-6	⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319	
CAS: 111-76-2	2-butoxyethanol	10-25%
EINECS: 203-905-0	⚠ Acute Tox. 4, H302; ⚠ Acute Tox. 4, H312; ⚠ Acute Tox. 4, H332; ⚠ Skin Irrit. 2, H315; ⚠ Eye Irrit. 2, H319	
CAS: 107-98-2	1-methoxy-2-propanol	10-25%
EINECS: 203-539-1	⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	
CAS: 123-86-4	n-butyl acetate	2,5-10%
EINECS: 204-658-1	⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.04.2016

Revision: 13.04.2016

Trade name: NC Beits Kleuren

(Contd. of page 2)

CAS: 67-56-1 EINECS: 200-659-6	methanol ⚠ Flam. Liq. 2, H225; ⚠ Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331; ⚠ STOT SE 1, H370	≤ 2,5%
CAS: 67-64-1 EINECS: 200-662-2	acetone ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	≤ 2,5%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

· **Description of first aid measures**

· **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Immediately remove any clothing soiled by the product.

· **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:** Rinse opened eye for several minutes under running water. If symptoms, consult a doctor.

· **After swallowing:**

Rinse out mouth.

Do not induce vomiting; call for medical help immediately.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Firefighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.

· **For safety reasons unsuitable extinguishing agents:** Water

· **Special hazards arising from the substance or mixture** No further relevant information available.

· **Advice for firefighters**

· **Protective equipment:**

Do not inhale explosion gases or combustion gases.

Wear self-contained respiratory protective device.

· **Additional information** Cool endangered receptacles with water spray.

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources.

· **Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.04.2016

Revision: 13.04.2016

Trade name: NC Beits Kleuren

(Contd. of page 3)

- **Reference to other sections**
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
- Ensure good ventilation/exhaustion at the workplace.
- Prevent formation of aerosols.
- Do not breathe vapour/spray.
- Avoid contact with skin and eyes.
- **Information about fire - and explosion protection:**
- Keep ignition sources away - Do not smoke.
- Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
- Keep container tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

107-98-2 1-methoxy-2-propanol

WEL	Short-term value: 560 mg/m ³ , 150 ppm
	Long-term value: 375 mg/m ³ , 100 ppm
	Sk

123-86-4 n-butyl acetate

WEL	Short-term value: 966 mg/m ³ , 200 ppm
	Long-term value: 724 mg/m ³ , 150 ppm

67-64-1 acetone

WEL	Short-term value: 3620 mg/m ³ , 1500 ppm
	Long-term value: 1210 mg/m ³ , 500 ppm

- **Ingredients with biological limit values:**

111-76-2 2-butoxyethanol

BMGV	240 mmol/mol creatinine
	Medium: urine
	Sampling time: post shift
	Parameter: butoxyacetic acid

- **Additional information:** The lists valid during the making were used as basis.

- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
- Keep away from foodstuffs, beverages and feed.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.04.2016

Revision: 13.04.2016

Trade name: NC Beits Kleuren

(Contd. of page 4)

Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· Form:	Fluid
· Colour:	Different according to colouring
· Odour:	Characteristic
· Odour threshold:	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

· Melting point/Melting range:	Undetermined.
· Boiling point/Boiling range:	78 °C

· **Flash point:** 13 °C

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 230 °C

· **Decomposition temperature:** Not determined.

· **Self-igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.04.2016

Revision: 13.04.2016

Trade name: NC Beits Kleuren

(Contd. of page 5)

· Explosion limits:	
Lower:	1,1 Vol %
Upper:	20,0 Vol %
· Vapour pressure at 20 °C:	59 hPa
· Density at 20 °C:	0,8825 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Fully miscible.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
VOC (EC)	88.65 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity**
Harmful if swallowed, in contact with skin or if inhaled.

· **LD/LC50 values relevant for classification:**

111-76-2 2-butoxyethanol

Oral	LD50	1300 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (guinea pig (cavia porcellus))
Inhalative	LC50/4 h	2 - 20 mg/l (rat)

67-56-1 methanol

Oral	LD50	> 2000 mg/kg (rat)
Dermal	LD50	> 2000 mg/kg (rabbit)
Inhalative	LC50/4 h	> 20 mg/l (rabbit)

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.04.2016

Revision: 13.04.2016

Trade name: NC Beits Kleuren

(Contd. of page 6)

- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause damage to organs. May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

12 Ecological information

- **Toxicity**

- **Aquatic toxicity:**

111-76-2 2-butoxyethanol

EC50/48 h (static)	1550 mg/l (daphnia magna)
LC50/96 h	1474 mg/l (fish (oncorhynchus mykiss))
NOEC (static)	100 mg/l (daphnia magna)
NOEC/21 d	> 100 mg/l (fish (danio rerio))
IC50	>1000 mg/l (bacteria)

67-56-1 methanol

EC50	> 500 mg/l (algea)
EC50/48 h	> 10000 mg/l (daphnia magna)
EC50/24 h	7600 mg/l (daphnia magna)
LC50/96 h	> 7900 mg/l (fish)

- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agents:** Water, if necessary together with cleansing agents.

GB

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31


Printing date 13.04.2016

Revision: 13.04.2016

Trade name: NC Beits Kleuren

(Contd. of page 7)

14 Transport information

· UN-Number · ADR, IMDG, IATA	UN1263
· UN proper shipping name · ADR · IMDG · IATA	1263 PAINT mixture PAINT Paint
· Transport hazard class(es) · ADR, IMDG, IATA	
· Class · Label	3 Flammable liquids. 3
· Packing group · ADR, IMDG, IATA	II
· Environmental hazards:	Not applicable.
· Special precautions for user · Danger code (Kemler): · EMS Number: · Stowage Category	Warning: Flammable liquids. 33 F-E, <u>S</u> -E B
· Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· Transport category · Tunnel restriction code	2 D/E
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1263 PAINT MIXTURE, 3, II

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- Named dangerous substances - ANNEX I methanol
- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.04.2016

Revision: 13.04.2016

Trade name: NC Beits Kleuren

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. of page 8)

16 Other information

The information provided in these documents are based on our current knowledge of this product and be in good faith and to the best of our knowledge. However, this information shall explicitly not as technical specification and do not constitute a guarantee of the properties. We do not accept any liability for damage or consequences of any kind or size, either express or implied, arising from the use of this data could result. Existing laws, rules and regulations by the receiver and user of the product be met on their own responsibility. They should also ensure that the product for the intended application and use.

· **Relevant phrases**

H225 Highly flammable liquid and vapour.
 H226 Flammable liquid and vapour.
 H301 Toxic if swallowed.
 H302 Harmful if swallowed.
 H311 Toxic in contact with skin.
 H312 Harmful in contact with skin.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H331 Toxic if inhaled.
 H332 Harmful if inhaled.
 H336 May cause drowsiness or dizziness.
 H370 Causes damage to organs.

· **Department issuing MSDS:** Product safety department.

· **Contact:** Laboratory

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 VOC: Volatile Organic Compounds (USA, EU)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 Flam. Liq. 2: Flammable liquids, Hazard Category 2
 Flam. Liq. 3: Flammable liquids, Hazard Category 3
 Acute Tox. 3: Acute toxicity, Hazard Category 3
 Acute Tox. 4: Acute toxicity, Hazard Category 4
 Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
 Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2
 STOT SE 1: Specific target organ toxicity - Single exposure, Hazard Category 1
 STOT SE 2: Specific target organ toxicity - Single exposure, Hazard Category 2
 STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

GB