

Page 1/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.11.2016 Revision: 02.11.2015

1 Identification of the substance/mixture and of the company/undertaking

· Product identifier

· Trade name: <u>Structuurolie Kleuren</u>

· Article number: 04.SOXXX.XX · Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture Wood preservatives

Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Wasziederij "De Vesting B.V."

Trasweg 12

NL-5712 BB Someren-Eind

The Netherlands Tel: +31 493 496760 Fax: +31 493 493670

Email: vesting@euronet.nl Web: www.vesting.nl

- Further information obtainable from: Product safety department.
- Emergency telephone number: During normal opening times: +31 493 496 760

2 Hazards identification

- · Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS07

STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

— GB



Printing date 09.11.2016 Revision: 02.11.2015

Trade name: Structuurolie Kleuren

· Hazard pictograms





GHS02 G

· Signal word Warning

Hazard statements

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing mist/vapours/spray.

P233 Keep container tightly closed.

P271 Use only outdoors or in a well-ventilated area.

P370+P378 In case of fire: Use for extinction: CO2, sand, extinguishing powder.

P405 Store locked up.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

VOC (EC) < 500 g/l (VOC-max. = 500 g/l (2010 A/i))

EUH066 Repeated exposure may cause skin dryness or cracking.

Contains 2-butanone oxime, cobalt bis(2-ethylhexanoate). May produce an allergic reaction.

- · Other hazards
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · **vPvB:** Not applicable.

3 Composition/information on ingredients

- · Chemical characterisation: Mixtures
- **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous component	s:	
CAS: 64742-48-9	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics	25-50%
EINECS: 265-150-3	♦ Asp. Tox. 1, H304	
CAS: 64742-48-9	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	10-25%
EINECS: 265-150-3	♦ Flam. Liq. 3, H226; ♦ Asp. Tox. 1, H304; ♦ STOT SE 3, H336	
EC number: 918-481-9	Hydrocarbons, C10-13, n-alkanes, isoalkanes, cyclics, <2% aromatics	2.5-10%
	♦ Asp. Tox. 1, H304	
CAS: 96-29-7	2-butanone oxime	≤ 2.5%
EINECS: 202-496-6	♦ Carc. 2, H351; ♦ Eye Dam. 1, H318; ♦ Acute Tox. 4, H312; Skin Sens. 1, H317	
CAS: 136-52-7	cobalt bis(2-ethylhexanoate)	≤ 2.5%
EINECS: 205-250-6	Repr. 2, H361f; Aquatic Acute 1, H400; Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic 3, H412	

• Additional information: For the wording of the listed hazard phrases refer to section 16.

GB

(Contd. of page 1)

Printing date 09.11.2016 Revision: 02.11.2015

Trade name: Structuurolie Kleuren

(Contd. of page 2)

4 First aid measures

- · Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Consult doctor in case of irritation.

- · After eye contact: Rinse opened eye for several minutes under running water. Consult a doctor.
- After swallowing:

Rinse out mouth.

Do not induce vomiting; call for medical help immediately.

- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Firefighting measures

- · Extinguishing media
- Suitable extinguishing agents:

Water haze

Carbon dioxide

Sand

Fire-extinguishing powder

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- \cdot Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Carbon monoxide (CO)

Carbon dioxide (CO2)

- · Advice for firefighters
- Protective equipment:

Wear fully protective suit.

Do not inhale explosion gases or combustion gases.

Wear self-contained respiratory protective device.

Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources.

· Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Do not allow to penetrate the ground/soil.

Inform respective authorities in case of seepage into water course or sewage system.

Methods and material for containment and cleaning up:

Absorb with non flammablel liquid-binding material.

Ensure adequate ventilation.

Clean the affected area carefully; suitable cleaners are:

(Contd. on page 4)

Printing date 09.11.2016 Revision: 02.11.2015

Trade name: Structuurolie Kleuren

(Contd. of page 3)

Organic solvent

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Keep away from heat and direct sunlight.

Avoid contact with skin and eyes.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- Information about storage in one common storage facility:

Do not store together with alkalis (caustic solutions).

Do not store together with oxidising and acidic materials.

- Further information about storage conditions: Store in cool, dry conditions in well sealed receptacles.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters

·Ingre	· Ingredients with limit values that require monitoring at the workplace:				
Hydro	Hydrocarbons, C10-13, n-alkanes, isoalkanes, cyclics, <2% aromatics				
TGG	Long-term value: 1000 mg/m³				
136-5	2-7 cobalt bis(2-ethylhexanoate)				
	Long-term value: 0.1 mg/m ³				
	as Co; Carc				

- Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

Avoid contact with the eyes and skin.

Do not eat, drink, smoke or sniff while working.

Do not carry product impregnated cleaning cloths in trouser pockets.

- Respiratory protection: Use suitable respiratory protective device in case of insufficient ventilation.
- Protection of hands: Avoid contact else wear gloves.
- · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

(Contd. on page 5)

Printing date 09.11.2016 Revision: 02.11.2015

Trade name: Structuurolie Kleuren

· Penetration time of glove material

(Contd. of page 4)

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:

Kinematic at 20 °C:

· Other information



Tightly sealed goggles

Information on basic physical and	chemical properties
General Information	
Appearance:	PL: 1
Form: Colour:	Fluid Different according to colouring
· Odour:	Different according to colouring Characteristic
· Odour threshold:	Not determined.
pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Undetermined.
· Flash point:	50 °C
· Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	> 200 °C
Decomposition temperature:	Not determined.
· Self-igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive ai vapour mixtures are possible.
Explosion limits:	
Lower:	0.6 Vol %
Upper:	7.0 Vol %
· Vapour pressure at 20 °C:	1010 hPa
Density at 20 °C:	0.89 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/wat	ter): Not determined.
· Viscosity:	N. 1
Dynamic:	Not determined.

>18 s (DIN 53211/4)

No further relevant information available.

Printing date 09.11.2016 Revision: 02.11.2015

Trade name: Structuurolie Kleuren

(Contd. of page 5)

10 Stability and reactivity

- · Reactivity No further relevant information available.
- Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions Reacts with acids, alkalis and oxidising agents.
- Conditions to avoid No further relevant information available.
- · **Incompatible materials:** No further relevant information available.
- · Hazardous decomposition products: Carbon monoxide and carbon dioxide

11 Toxicological information

- · Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	· LD/LC50 values relevant for classification:					
64742-48-9 Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics						
Oral	LD50	>5000 mg/kg (rat)				
Dermal	LD50	>5000 mg/kg (rabbit)				
Inhalative	LC50/4 h	4951 mg/l (rat)				
64742-48-	9 Hydroca	arbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics				
Oral	LD50	> 5000 mg/kg (rat)				
Dermal	LD50	> 5000 mg/kg (rabbit)				

- Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure
- May cause drowsiness or dizziness.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

12 Ecological information

· Toxicity

· Aquatic toxicity:

64742-48-9 Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

EC50/48 h > 100 mg/l (daphnia) LC50/96 h > 100 mg/l (fish)

- Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

(Contd. on page 7)

Printing date 09.11.2016 Revision: 02.11.2015

Trade name: Structuurolie Kleuren

(Contd. of page 6)

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- **Recommendation:** Disposal must be made according to official regulations.

Transport information	
UN-Number ADR, IMDG, IATA	UN1263
UN proper shipping name ADR IMDG, IATA	1263 PAINT PAINT
Transport hazard class(es)	
ADR, IMDG, IATA	
Class Label	3 Flammable liquids.3
Packing group ADR, IMDG, IATA	III
Environmental hazards: Marine pollutant:	No
Special precautions for user Danger code (Kemler): EMS Number:	Warning: Flammable liquids. 30 F-E, <u>S-E</u>
Transport in bulk according to Annex I and the IBC Code	I of Marpol Not applicable.
Transport/Additional information:	
ADR Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
Transport category Tunnel restriction code	3 D/E

Printing date 09.11.2016 Revision: 02.11.2015

Trade name: Structuurolie Kleuren

· IMDG
· Limited quantities (LQ) 5L
· Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

(Contd. of page 7)

UN "Model Regulation": UN1263, PAINT, 3, III

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

The information provided in these documents are based on our current knowledge of this product and be in good faith and to the best of our knowledge. However, this information shall explicitly not as technical specification and do not constitute a guarantee of the properties. We do not accept any liability for damage or consequences of any kind or size, either express or implied, arising from the use of this data could result. Existing laws, rules and regulations by the receiver and user of the product be met on their own responsibility. They should also ensure that the product for the intended application and use.

· Relevant phrases

- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H351 Suspected of causing cancer.
- H361f Suspected of damaging fertility.
- H400 Very toxic to aquatic life.
- H412 Harmful to aquatic life with long lasting effects.
- · Department issuing SDS: Product safety department.
- · Contact: Laboratory
- Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity - Category 4

(Contd. on page 9)

Printing date 09.11.2016 Revision: 02.11.2015

Trade name: Structuurolie Kleuren

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Carc. 2: Carcinogenicity – Category 2 Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

(Contd. of page 8)