

Page 1/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.11.2015 Revision: 29.10.2015

1 Identification of the substance/mixture and of the company/undertaking

· Product identifier

· Trade name: Wasolie 1000 Naturel · Article number: 04.WO1000.XX

· Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture Wood preservatives

Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Wasziederij "De Vesting B.V."

Trasweg 12

NL-5712 BB Someren-Eind

The Netherlands Tel: +31 493 496760 Fax: +31 493 493670

Email: vesting@euronet.nl Web: www.vesting.nl

- Further information obtainable from: Product safety department.
- Emergency telephone number: During normal opening times: +31 493 496 760

2 Hazards identification

- · Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS07

STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

— GE



Printing date 11.11.2015 Revision: 29.10.2015

Trade name: Wasolie 1000 Naturel

· Hazard pictograms





GHS02 GHS0

· Signal word Warning

· Hazard-determining components of labelling:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

· Hazard statements

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing mist/vapours/spray.

P233 Keep container tightly closed.

P271 Use only outdoors or in a well-ventilated area.

P370+P378 In case of fire: Use for extinction: CO2, sand, extinguishing powder.

P405 Store locked up.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Additional information:

VOC (EC) < 500 g/l (VOC-max. = 500 g/l (2010 A/i))

EUH066 Repeated exposure may cause skin dryness or cracking.

Contains 2-butanone oxime. May produce an allergic reaction.

- · Other hazards
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · **vPvB:** Not applicable.

3 Composition/information on ingredients

- · Chemical characterisation: Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous component	s:	
CAS: 64742-48-9	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics	25-50%
EINECS: 265-150-3	♦ Asp. Tox. 1, H304	
CAS: 64742-48-9	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	10-25%
EINECS: 265-150-3	♦ Flam. Liq. 3, H226; ♦ Asp. Tox. 1, H304; ♦ STOT SE 3, H336	
ELINCS: 432-430-3	reaction mass of: N,N'-ethane-1,2-diylbis(hexanamide); 12-hydroxy-N-[2-	≤ 2.5%
	[(1-oxyhexyl)amino]ethyl]octadecanamide; N,N'-ethane-1,2-diylbis(12-	
	hydroxyoctadecanamide)	
	Aquatic Chronic 4, H413	
EC number: 918-481-9	Hydrocarbons, C10-13, n-alkanes, isoalkanes, cyclics, <2% aromatics	≤ 2.5%
	♦ Asp. Tox. 1, H304	
CAS: 96-29-7	2-butanone oxime	≤ 2.5%
EINECS: 202-496-6	♦ Carc. 2, H351; ♦ Eye Dam. 1, H318; ♦ Acute Tox. 4, H312; Skin Sens 1, H317	-
	(Conto	l. on page 3

— GB

(Contd. of page 1)

Printing date 11.11.2015 Revision: 29.10.2015

Trade name: Wasolie 1000 Naturel

(Contd. of page 2)

· Additional information: For the wording of the listed risk phrases refer to section 16.

4 First aid measures

- · Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Consult doctor in case of irritation.

- · After eye contact: Rinse opened eye for several minutes under running water. Consult a doctor.
- · After swallowing:

Rinse out mouth.

Do not induce vomiting; call for medical help immediately.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Firefighting measures

- Extinguishing media
- · Suitable extinguishing agents:

Water haze

Carbon dioxide

Foam

Fire-extinguishing powder

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- \cdot Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Carbon monoxide (CO)

Carbon dioxide (CO2)

- · Advice for firefighters
- · Protective equipment:

Do not inhale explosion gases or combustion gases.

Wear self-contained respiratory protective device.

Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

6 Accidental release measures

 \cdot Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Wear protective equipment. Keep unprotected persons away.

Particular danger of slipping on leaked/spilled product.

Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Do not allow to penetrate the ground/soil.

Inform respective authorities in case of seepage into water course or sewage system.

Methods and material for containment and cleaning up:

Absorb with non flammablel liquid-binding material.

Ensure adequate ventilation.

(Contd. on page 4)

Printing date 11.11.2015 Revision: 29.10.2015

Trade name: Wasolie 1000 Naturel

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Do not breathe vapour/spray.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- Information about storage in one common storage facility:

Do not store together with alkalis (caustic solutions).

Do not store together with oxidising and acidic materials.

- Further information about storage conditions: Store in cool, dry conditions in well sealed receptacles.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters
- Ingredients with limit values that require monitoring at the workplace:

Hydrocarbons, C10-13, n-alkanes, isoalkanes, cyclics, <2% aromatics

TGG | Long-term value: 1000 mg/m³

- Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Do not eat, drink, smoke or sniff while working.

- Respiratory protection: Use suitable respiratory protective device in case of insufficient ventilation.
- · Protection of hands: Avoid contact else wear gloves.
- · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.


(Contd. on page 5)

(Contd. of page 3)

Printing date 11.11.2015 Revision: 29.10.2015

Trade name: Wasolie 1000 Naturel

· Eye protection:



9 Physical and chemical properties · Information on basic physical and chemical properties · General Information · Appearance: Form: Fluid Colour: Light brown · Odour: Characteristic · Odour threshold: Not determined. Not determined. · pH-value: · Change in condition Melting point/Melting range: Undetermined. 142 °C **Boiling point/Boiling range:** 48 °C · Flash point: Not applicable. · Flammability (solid, gaseous): > 200 °C Ignition temperature: Not determined. **Decomposition temperature:** · Self-igniting: Product is not selfigniting. Product is not explosive. However, formation of explosive air/ Danger of explosion: vapour mixtures are possible. **Explosion limits:** Lower: 0.6 Vol % 7.0 Vol % Upper: · Vapour pressure at 20 °C: 1010 hPa Density at 20 °C: 0.880 g/cm3 Not determined. · Relative density · Vapour density Not determined. · Evaporation rate Not determined. · Solubility in / Miscibility with Not miscible or difficult to mix. · Partition coefficient (n-octanol/water): Not determined. Dynamic at 20 °C: 50 mPas **Kinematic:** Not determined. · Solvent content: **Organic solvents:** 52.5 % VOC (EC) 52.50 % **Solids content:** 46.0 %

(Contd. on page 6)

(Contd. of page 4)

Printing date 11.11.2015 Revision: 29.10.2015

Trade name: Wasolie 1000 Naturel

(Contd. of page 5)

• **Other information** No further relevant information available.

10 Stability and reactivity

- Reactivity
- Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions Reacts with acids, alkalis and oxidising agents.
- Conditions to avoid No further relevant information available.
- · **Incompatible materials:** No further relevant information available.
- Hazardous decomposition products:

Carbon dioxide

Carbon monoxide

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity

reductionally					
· LD/LC50	LD/LC50 values relevant for classification:				
64742-48-9 Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics					
Oral	LD50	>5000 mg/kg (rat)			
Dermal	LD50	>5000 mg/kg (rabbit)			
Inhalative	LC50/4 h	4951 mg/l (rat)			
64742-48-	9 Hydroca	arbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics			
Oral	LD50	> 5000 mg/kg (rat)			
Dermal	LD50	> 5000 mg/kg (rabbit)			
96-29-7 2-butanone oxime					
Dermal	LD50	1100 mg/kg (-)			

- Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

12 Ecological information

· Toxicity

	· Aquatic to	xicity:
	64742-48-9	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics
Ī	EC50/48 h	> 100 mg/l (daphnia)
I	LC50/96 h	> 100 mg/l (fish)

(Contd. on page 7)

Printing date 11.11.2015 Revision: 29.10.2015

Trade name: Wasolie 1000 Naturel

(Contd. of page 6

	(Conta. of page 6)
96-29-7 2	butanone oxime
EC50/48 l	a 201 mg/l (daphnia magna)
IC50/72 h	6.1 mg/l (algea (selenastrum capricornutum))
LC50/96 ł	>100 mg/l (fish (oryzias latipes))

- Persistence and degradability No further relevant information available.
- Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system, even in small quantities. Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

- Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 01 11* waste paint and varnish containing organic solvents or other dangerous substances

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

· UN-Number · ADR, IMDG, IATA	UN1263
· UN proper shipping name · ADR	1263 PAINT
· IMDG, IATA	PAINT
· Transport hazard class(es)	
· ADR, IMDG, IATA	

· Class	3 Flammable liquids

Class Label	3 Flammable liquids.
· Packing group · ADR, IMDG, IATA	III
· Environmental hazards: · Marine pollutant:	No
· Special precautions for user · Danger code (Kemler):	Warning: Flammable liquids. 30

(Contd. on page 8)

Printing date 11.11.2015 Revision: 29.10.2015

Trade name: Wasolie 1000 Naturel

	(Contd. of page
· EMS Number:	F-E, <u>S-E</u>
· Transport in bulk according to Annex	II of
MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
• • •	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code	D/E
· IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
• • •	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN1263, PAINT, 3, III

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

The information provided in these documents are based on our current knowledge of this product and be in good faith and to the best of our knowledge. However, this information shall explicitly not as technical specification and do not constitute a guarantee of the properties. We do not accept any liability for damage or consequences of any kind or size, either express or implied, arising from the use of this data could result. Existing laws, rules and regulations by the receiver and user of the product be met on their own responsibility. They should also ensure that the product for the intended application and use.

· Relevant phrases

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

H413 May cause long lasting harmful effects to aquatic life.

- · Department issuing MSDS: Product safety department.
- · Contact: Laboratory
- Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

(Contd. on page 9)

Printing date 11.11.2015 Revision: 29.10.2015

Trade name: Wasolie 1000 Naturel

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Acute Tox. 4: Acute toxicity, Hazard Category 4
Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Carc. 2: Carcinogenicity, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

Aquatic Chronic 4: Hazardous to the aquatic environment - Chronic Hazard, Category 4

(Contd. of page 8)