

Page 1/8

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 12.07.2016 Revision: 30.03.2016

1 Identification of the substance/mixture and of the company/undertaking

· Product identifier

· Trade name: <u>UV-LED AC Reiniger</u> · Article number: 03.UVACC.XX

· CAS Number:

67-64-1 • EC number: 200-662-2

· Index number: 606-001-00-8

• Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.

- · Application of the substance / the mixture Cleaning material/ Detergent
- Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Wasziederij "De Vesting B.V."

Trasweg 12

NL-5712 BB Someren-Eind

The Netherlands Tel: +31 493 496760 Fax: +31 493 493670

Email: vesting@euronet.nl Web: www.vesting.nl

- · Further information obtainable from: Product safety department.
- Emergency telephone number: During normal opening times: +31 493 496 760

2 Hazards identification

- · Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

(Contd. on page 2)





Revision: 30.03.2016 Printing date 12.07.2016

Trade name: UV-LED AC Reiniger

(Contd. of page 1)

- · Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The substance is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02

· Signal word Danger

· Hazard-determining components of labelling:

acetone

Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

Wear protective gloves/protective clothing/eye protection/face protection. P280

P243 Take precautionary measures against static discharge.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention. P337+P313

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international P501

regulations.

Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

Restricted to professional users. Keep out of the reach of children

Other hazards

· Results of PBT and vPvB assessment

• **PBT:** Not applicable. · **vPvB:** Not applicable.

3 Composition/information on ingredients

· Chemical characterisation: Substances

· CAS No. Description

67-64-1 acetone

· Identification number(s) · EC number: 200-662-2

· Index number: 606-001-00-8

4 First aid measures

- Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

(Contd. on page 3)

Printing date 12.07.2016 Revision: 30.03.2016

Trade name: UV-LED AC Reiniger

· After skin contact:

Immediately rinse with water.

Consult doctor in case of irritation.

- · After eye contact: Rinse opened eye for several minutes under running water. Consult a doctor.
- · After swallowing:

Rinse out mouth.

Do not induce vomiting; call for medical help immediately.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Firefighting measures

- · Extinguishing media
- Suitable extinguishing agents:

Fire-extinguishing powder

Alcohol resistant foam

Carbon dioxide

Water spray

- For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture

Carbon monoxide (CO)

Carbon dioxide (CO2)

- Advice for firefighters
- Protective equipment:

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

· Additional information Cool endangered receptacles with water spray.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

Ensure adequate ventilation

Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- Precautions for safe handling

Avoid contact with skin and eyes.

Store in cool, dry place in tightly closed receptacles.

Work only in fume cupboard.

Do not breathe vapours.

(Contd. on page 4)

(Contd. of page 2)

Printing date 12.07.2016 Revision: 30.03.2016

Trade name: UV-LED AC Reiniger

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- Information about storage in one common storage facility:

Do not store together with alkalis (caustic solutions).

Store away from oxidising agents.

· Further information about storage conditions:

Keep container tightly sealed.

Protect from heat and direct sunlight.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters

Ingredients with limit values that require monitoring at the workplace:

67-64-1 acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Do not eat, drink, smoke or sniff while working.

Do not carry product impregnated cleaning cloths in trouser pockets.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Respiratory protection:

Short term filter device:

Filter AX

· Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Butyl rubber, BR

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

(Contd. of page 3)

Printing date 12.07.2016 Revision: 30.03.2016

Trade name: UV-LED AC Reiniger

· Eye protection:





Tightly sealed goggles

9 Physical and chemical proper	ties	
· Information on basic physical and chemical properties · General Information · Appearance:		
Form:	Fluid	
Colour:	Colourless	
Odour:	Aromatic	
· Odour threshold:	Not determined.	
· pH-value:	Not determined.	
· Change in condition Melting point/Melting range: Boiling point/Boiling range:	-94.7 °C 55.8-56.6 °C	
· Flash point:	<-18 °C	
· Flammability (solid, gaseous):	Not applicable.	
· Ignition temperature:	465 °C	
· Decomposition temperature:	Not determined.	
· Self-igniting:	Not determined.	
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.	
· Explosion limits:		
Lower:	2.6 Vol %	
Upper:	13 Vol %	
· Vapour pressure at 20 °C:	233 hPa	
Density at 20 °C:	0.7915 g/cm ³	
Relative density	Not determined.	
Vapour density	Not determined.	
· Evaporation rate	Not determined.	
Solubility in / Miscibility with water:	Fully miscible.	
· Partition coefficient (n-octanol/wate	Partition coefficient (n-octanol/water): Not determined.	
· Viscosity: Dynamic at 25 °C: Kinematic:	32 mPas Not determined.	
· Solvent content:		
Organic solvents:	100.0 %	
VOC (EC)	100.00 %	
· Other information	No further relevant information available.	

GR ·

Printing date 12.07.2016 Revision: 30.03.2016

Trade name: UV-LED AC Reiniger

(Contd. of page 5)

10 Stability and reactivity

- · Reactivity No further relevant information available.
- Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions

Possible formation of peroxide.

Reacts with oxidising agents.

Reacts with alkali (lyes).

- Conditions to avoid No further relevant information available.
- · **Incompatible materials:** No further relevant information available.
- · Hazardous decomposition products: Carbon monoxide and carbon dioxide

11 Toxicological information

- Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:			
67-64-1 acetone			
Oral	LD50	5800 mg/kg (rat)	
Dermal	LD50	15800 mg/kg (rabbit)	
Inhalative	LC50/4 h	76 mg/l (rat)	

- Primary irritant effect:
- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

12 Ecological information

Toxicity

Tomercy		
· Aquatic toxicity:		
67-64-1 ac	etone	
EC50/48 h	8800 mg/l (daphania pulex)	
LC50/96 h	5540 mg/l (fish (oncorhynchus mykiss))	
NOEC/8 d	530 mg/l (algea (microcystis aeruginosa))	

- Persistence and degradability Easily biodegradable
- Behaviour in environmental systems:
- · Bioaccumulative potential

Due to the distribution coefficient n-octanol/water an accumulation in organisms is not expected.

- Mobility in soil If the product gets into the soil, it is very mobile and can contaminate the groundwater.
- Additional ecological information:
- · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

(Contd. on page 7)

Printing date 12.07.2016 Revision: 30.03.2016

Trade name: UV-LED AC Reiniger

(Contd. of page 6)

- Water hazard class 1 (German Regulation) (Assessment by list): slightly hazardous for water
- Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- **Recommendation:** Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

Tuananautinfaumatian	
Transport information	
· UN-Number · ADR, IMDG, IATA	UN1090
· UN proper shipping name	
ADR	1090 ACETONE
· IMDG · IATA	ACETONE Acetone
	rectone
Transport hazard class(es)	
· ADR, IMDG, IATA	
· Class	3 Flammable liquids.
· Label	3
· Packing group	
ADR, IMDG, IATA	II
Environmental hazards:	Not applicable.
Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler):	33
EMS Number:	F-E,S-D
Stowage Category	E
Transport in bulk according to Annex II of	
and the IBC Code	Not applicable.
Transport/Additional information:	
· ADR	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· Transport category	2
Tunnel restriction code	D/E
	(Contd. on page

Printing date 12.07.2016 Revision: 30.03.2016

Trade name: UV-LED AC Reiniger

(Contd. of page 7)

· IMDG

· Limited quantities (LQ)

· Excepted quantities (EQ)

1L Code: E2

Code: E2

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

• UN "Model Regulation": UN 1090 ACETONE, 3, II

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I Substance is not listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

The information provided in these documents are based on our current knowledge of this product and be in good faith and to the best of our knowledge. However, this information shall explicitly not as technical specification and do not constitute a guarantee of the properties. We do not accept any liability for damage or consequences of any kind or size, either express or implied, arising from the use of this data could result. Existing laws, rules and regulations by the receiver and user of the product be met on their own responsibility. They should also ensure that the product for the intended application and use.

- · Department issuing SDS: Product safety department.
- · Contact: Laboratory
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

- GB